



VICINITY MAP
1"= 1/4 mile

EXISTING TREES WITHIN PROPERTY BOUNDARIES TO REMAIN				
TAG	SIZE	TYPE	CITY CREDITS	CAL POINTS
4155	11	LIVE OAK	100%	11
4166	21	CHINABERRY	150%	32
4167	22	ELM	150%	33
4168	8	ELM	100%	8
4170	24	ELM	150%	36
4173	11	CEDAR	100%	11
4206	23	CEDAR	150%	35
4214	9	LIVE OAK	115%	10
4215	8	LIVE OAK	115%	9
4217	8	LIVE OAK	115%	9
4218	10	LIVE OAK	115%	12
4219	8	LIVE OAK	115%	9
4220	9	LIVE OAK	115%	10
4221	10	LIVE OAK	115%	12
4224	14	CEDAR	150%	21
4225	15	CEDAR	150%	23

EXISTING TREES WITHIN PROPERTY BOUNDARIES TO REMAIN				
TAG	SIZE	TYPE	CITY CREDITS	CAL POINTS
4226	11	CEDAR	115%	13
4243	23	LIVE OAK	150%	35
4244	19	LIVE OAK	150%	29
4245	27	LIVE OAK	150%	41
4246	15	ELM	150%	23
4247	11	ELM	100%	11
4248	8	ELM	100%	8
4258	11	CEDAR	100%	11
4259	9	LIVE OAK	115%	10
4260	9	CEDAR	115%	10
4261	9	LIVE OAK	115%	10
4262	12	CEDAR	150%	18
4265	13	CEDAR	150%	20
4266	8	CEDAR	100%	8
4267	0	10" CEDAR - DEAD	0%	0
4268	14	CEDAR	150%	21
(A)	410	TOTAL CAL INCHES W/CREDITS:	(B)	546

EXISTING TREES WITHIN PROPERTY BOUNDARIES TO BE REMOVED		
TAG	SIZE	TYPE
4154	16	LIVE OAK
4156	14	CEDAR
4160	14	ELM
4161	26	COTTONWOOD
4163	26	COTTONWOOD
4164	12	BOIS D'ARC (OSAGE ORANGE)
4216	11	LIVE OAK

(C) 119 : TOTAL CALIPER INCHES

MITIGATION CALCULATIONS	
TOTAL EXISTING SITE CALIPER INCHES : (A+C)	529 (D)
PRESERVED SITE CALIPER INCHES : (A)	410 (A)
PRESERVED SITE CALIPER INCHES WITH CREDITS : (B)	546 (B)
PERCENT PRESERVED SITE CALIPER INCHES WITH CREDITS : (B / D)	103.2%

ROW TREES TO REMAIN		
TAG	SIZE	TYPE
4222	22	HACKBERRY
4249	12	LIVE OAK
4254	16	CEDAR
4257	11	CEDAR

TREE PRESERVATION NOTES

- ALL EXISTING TREES TO BE PRESERVED SHALL BE PROTECTED AT THE ROOT PROTECTION ZONE (RPZ). THE RPZ SHALL BE DETERMINED BY TREE SIZE (12" [1.0'] RADIUS FROM TRUNK FOR EVERY 1" DIAMETER OF TRUNK AT 4.5' FROM GROUND).
- A CHAINLINK OR ORANGE MESH FENCE BARRIER AROUND THE RPZ SHALL BE ERECTED BEFORE SITE WORK IS INITIATED AND MAINTAINED UNTIL CONSTRUCTION IS COMPLETED.
- RPZ SHALL BE SUSTAINED IN A NATURAL STATE AND SHALL BE FREE FROM VEHICULAR OR MECHANICAL TRAFFIC; NO FILL, EQUIPMENT, LIQUIDS, OR CONSTRUCTION DEBRIS SHALL BE PLACED INSIDE THE PROTECTIVE BARRIER.
- THE RPZ SHALL BE COVERED WITH 6" OF COARSE MULCH TO REDUCE MOISTURE STRESS.
- ANY DAMAGE DONE TO EXISTING TREE CROWNS OR ROOTS SYSTEMS SHALL BE REPAIRED IMMEDIATELY. ALL WOUNDS TO OAK TREES SHALL BE PAINTED WITH PRUNING PAINT WITHIN 30 MINUTES AFTER DAMAGE. ROOTS EXPOSED DURING CONSTRUCTION SHALL BE CUT CLEANLY.
- THE PROPOSED FINISHED GRADE AND ELEVATION OF LAND WITHIN THE RPZ OF ANY TREE TO BE PRESERVED SHALL NOT BE RAISED OR LOWERED MORE THAN 3". WELLING AND RETAINING METHODS ARE ALLOWED OUTSIDE THE RPZ.
- THE RPZ SHALL REMAIN PERVIOUS, I.E. GROUND COVER OR TURF AT COMPLETION OF LANDSCAPE DESIGN.

EXISTING TREE PLAN LEGEND

- EXISTING TREE TO REMAIN (WITHIN PROPERTY BOUNDARIES)
- EXISTING TREE TO BE REMOVED (WITHIN PROPERTY BOUNDARIES)

